



# SCARBOROUGH COMMUNITY MULTICULTURAL FESTIVAL

## VENDER POWER REQUIREMENTS

PLEASE FILL OUT BELOW AND RETURN PRIOR TO EVENT SETUP

VENDER \_\_\_\_\_

COMMENTS \_\_\_\_\_

POWER WILL BE PROVIDED TO EDGE OF TENT / TRAILER. NO EXTENTION CORDS WILL BE PROVIDED  
PLEASE REFER TO FOLLOWING PAGES FOR RECOGNIZED CERTIFICATION MARKS  
AND RECEPTACLE CONFIGURATIONS. TO HELP IN COMPLETING THE CHART BELOW.

EXAMPLE:

AMPERAGE	VOLTAGE	QTY	PLUG TYPE	ITEM
15 A	110 V		U-GROUND (5-15R)	2 COFFEE, LIGHTS, FRIDGE
	2 POLE 3 WIRE		TWIST (L5-15R)	
	250 V		BLADE (6-15R)	FOOD WARMERS
	2 POLE 3 WIRE		TWIST (L6-15R)	

AMPERAGE	VOLTAGE	QTY	PLUG TYPE	ITEM
15 A	110 V		U-GROUND (5-15R)	
	2 POLE 3 WIRE		TWIST (L5-15R)	
	250 V		BLADE (6-15R)	
	2 POLE 3 WIRE		TWIST (L6-15R)	
20 A	110 V		BLADE (6-20R)	
	2 POLE 3 WIRE		TWIST (L5-20R)	
	250 V		BLADE (6-20R)	
	2 POLE 3 WIRE		TWIST (L6-20R)	
30 A	110 V		RV PLUG (TT-30)	
	2 POLE 3 WIRE		TWIST (L5-30R)	
	250 V		BLADE (6-30R)	
	2 POLE 3 WIRE		TWIST (L6-30R)	
	110/208 V		DRYER (14-30R)	
50 A	3 POLE 4 WIRE		TWIST (L14-30R)	
	110/208 V		STOVE (14-50R)	
	3 POLE 4 WIRE		TWIST (CS6364/65)	
100 A	110/208 V	3 POLE 4 WIRE	BARE TAILS	
			CAMLOCK MINI	
			CAMLOCK	
	BARE TAILS			
	3 PHASE		PIN AND SLEEVE	
	4 POLE 5 WIRE		BARE TAILS	
	347/600 V		CAMLOCK	
	3 PHASE		BARE TAILS	
4 POLE 5 WIRE		PIN AND SLEEVE		

**NOTE: - ALL PANELS AND/OR ASSEMBLIES MUST HAVE A RECOGNIZED FIELD EVALUATION AGENCY STICKER FOR TERMINATION AND POWER UP.  
-ALL EQUIPMENT / DEVICES MUST HAVE A RECOGNIZED CERTIFICATION**

**PLEASE CALL 1-877-ESA-SAFE FOR PANEL OR ASSEMBLY INSPECTION PRIOR TO EVENT IF YOU DO NOT HAVE A STICKER.**

## Recognized Certification Marks

### Recognized Field Evaluation Agency Markings



### Recognized Certification Markings



**SAFETY NEWS**



**Protecting The Ontario Public From Electrical Hazards.**

For information on electrical safety, electrical installations or to request an electrical inspection please contact the

**Customer Service Centre**  
(Business Hours 7:00am-6:30pm)

**1-877-372-7233**  
**(1-877-ESA-SAFE)**




























Additional Contact Numbers

[CLICK HERE >>>](#)




please circle the plug that match your electrical needs.

### RECPACLE CONFIGURATIONS

CURRENT RATING	TYPE	2 POLE - 2 WIRE NO GROUND		2 POLE - 3 WIRE GROUNDING		3 POLE 4 WIRE GROUNDING
		125V	250V	125V	250V	125/250V
15A	STRAIGHT BLADE	 1-15R	 2-15R	 5-15R	 6-15R	
	TWIST-LOCK	 L1-15R		 L5-15R	 L6-15R	
20A	STRAIGHT BLADE		 2-20R	 5-20R	 6-20R	 14-20R
	TWIST-LOCK		 L2-20R	 L5-20R	 L6-20R	 L14-20R
30A	STRAIGHT BLADE		 2-30R	 5-30R	 6-30R	 14-30R
	TWIST-LOCK			 L5-30R	 L6-30R	 L14-30R
50A	STRAIGHT BLADE			 5-50R	 6-50R	 14-50R
	TWIST-LOCK					 CS6364/65
60A	STRAIGHT BLADE					 14-60R
	TWIST-LOCK					

NOTES: 1) Female receptacles shown. For male plug change suffix from "R" to "P" and minor size.  
 2) For female connectors change suffix from "R" to "C".  
 3) Twist-Lock 50A CS6364 connector and CS6365 plug are not NEMA.  
 4) Normally G = ground (green), W = neutral (white), X & Y = hot (red & black).

COMMON 50 AMP TWIST  
110/208V 3 POLE 4 WIRE



RV Receptacle  
30 Amp  
120VAC

